

SIESTA



A compact window awning suitable for most buildings. Standard internal or external operation with terylene tape. Drop arms with adjustable springs always

ensure the correct fabric tension. A stylish aluminium cassette protects the fabric from the elements.

SIESTA

Window awning

Operation

External or internal operation with polyester tape. The tape is guided through the window frame, even if the awning is wider than the window, by a specially designed optional tape guide. For storage and protection of the tape, add the optional tape coil box.

Installation

The awning can easily be installed directly on to the window architrave, the wall or into a recess. Optional recess brackets allow 45–185 mm depth adjustment.

Drop arms

Drop arms with adjustable springs ensure the correct fabric tension. Optional wind locking drop arms are recommended for awnings exposed to strong winds.

Components

The selection of anti-corrosion and highly durable materials allows us to offer you a comprehensive warranty. No maintenance required.

Fabric

Choose from a wide collection ranging from solid colour to block stripes and designed patterns. Select fabric, finish and trimmings for the removable valance.

Dimensions

Projection: 0.5, 0.6, 0.7, 0.8, 0.9, 1.0 m.

Maximum width: 3.2 m per unit.



Aluminium cassette protects the fabric from the elements.



Drop arms with adjustable springs for correct fabric tension.



Internal and external operation with polyester tape, motorisation as option.